

**Industrial SD card** 



## Apacer

# Industrial SD card

#### **Overview**

The Apacer industrial SD features with high reliability and resistance to extended temperatures be widely applied to industrial, military, communication, surveillance, medical devices and car navigation, thereby satisfying the storage need of demanding industrial enterprises.



The series of SD-M adopts vendor guaranteed wide-temp MLC chips for the highest reliability, while the firmware and controller can be tailored to customer's specifications and verification, which reduces the risk of compatibility. To ensure that data stay correct, the industrial SD card supports 24-bit ECC function, which minimizes potential errors led by frequent data access to strengthen the system reliability. Also complete with integrated Global Wear leveling and S.M.A.R.T technology, the SD card features a prolonged lifespan as well as safer data storage.

#### **Feature**

- Industrial Grade SD card
- S.M.A.R.T supported
- Wear-Leveling and Block Management
- Auto Standby and Sleep Mode Support
- Golden finger 30u"



## **Specifications**

Model	Industrial SD-M	
Interface	SD2.0	
NAND Flash Type	MLC	
Capacity	SDHC:4GB~32GB	
Sustained Read Performance (MB/sec)	Up to 19	
Sustained Write Performance (MB/sec)	Up to 8	
ECC Engine*	Built-in 24-bit per 1K bytes BCH ECC	
Standard Operating Temperature ( °C )	0~+70	
Extended Operating Temperature ( °C )	-40 ~ + 85	
Storage Temperature ( °C )	-40 ~ + 100	
Shock	1,000G, 0.5ms	
Vibration	10Hz~50Hz/3mm (frequency/displacement) 50Hz~2,000Hz/15G (frequency/accelerate)	
Humidity	95%	
Operating Voltage	3.3 V ± 5%	
Low Power Consumption	Active mode: 55 mA & Idle mode: 105 mA	
Dimension (L x W x H )	24x32x2.1 (mm)	
MTBF (hours)	>1,000,000	
Features / Technology	S.M.A.R.T./Wide Temp.	
Applications	Military/Cloud Computing/In- Vehicle/Gaming/HealthCare/Embedded System	

Vehicle/Gaming/HealthCare/Embedded System



### **Ordering Info**

Model	Standard temp: 0~70	Extended temp:-40~85
4G	AP-ISD04GCS4A-2CM	AP-ISD04GIS4B-2CM
8G	AP-ISD08GCS4A-2CM	AP-ISD08GIS4B-2CM
16G	AP-ISD16GCS4A-2CM	AP-ISD16GIS4B-2CM
32G	AP-ISD32GCD4A-2CM	AP-ISD32GID4B-2CM

#### **Global Presence**

Taiwan (Headquarters) Apacer Technology Inc. Tel: +886-2-2267-8000

Fax: +886-2-2267-2261

Japan

Apacer Technology Corp. Tel: +81-3-5419-2668 Fax: +81-3-5419-0018

Europe Apacer Technology B.V. Tel: +31-40-267-0000

Fax: +31-40-290-0686

Apacer Technologies Pvt. Ltd. Tel: +91-80-41529061~3 Fax: +91-80-41700215

U.S.A.

Apacer Memory America, Inc. Tel: +1-408-518-8699

Fax: 1-510-249-9551

China

Apacer Electronic(Shanghai)

Tel: +86-21-6228-9939