

Endurance Report

for Industrial SD/MicroSDHC H1-M

April 8, 2015

Version 1.0



Apacer Technology Inc.

1F., No.32., Zhongcheng Rd., Tucheng Dist., New Taipei City 236, Taiwan R.O.C

Tel: +886-2-2267-8000

Fax: +886-2-2267-2261

Endurance

Overview

Endurance encompasses the x-factor list in SSDs that determines the effective service life of an SSD and defines the amount of written data an SSD's ability of retentiveness before coming to the end of its rated life. There is no absolute one-to-one relationship between the number of host writes and the actual writes performed to the NAND, and not every NAND block reaches to the end of its life (rated maximum number of erases) concurrently. Since SSD endurance relies on the maximum erases for any of the blocks on the NAND, both the write amplification and wear leveling efficiency must be accounted for in determining an expected endurance rating.

SSD Endurance Impact List

Several factors impact the resulting SSD endurance including the efficiency of the wear leveling algorithms, the write efficiency (as write amplification), the cycling capability of the NAND components, and the nature of the applied workload.

Wear Leveling Efficiency

Wear leveling efficiency is defined as the ration of the average number of erases on all blocks across the entire SSD to the maximum erases on any block on the NAND. Hence, a formula concluded as below.

$$\text{WearLevelingEfficiency} = \frac{\text{AverageErasesAcrossAllBlocks}}{\text{MaximumErasesOnAnyBlock}}$$

Write Amplification

The amount of data written to the NAND components is usually greater than the amount of data written by the host. A number of different factors contribute to the amount of data written to the NAND exceeding the amount written by the host including such NAND management functions as wear leveling.

Write amplification is defined as the amount of data written to the NAND divided by the amount of data written by the host for a given host input stimulus such as below.

$$\text{WriteAmp} = \frac{\text{TotalDataWrittenToNAND}}{\text{TotalDataWrittenByHost}}$$

NAND Cycling Capability

At SSD level, the NAND cycling capability will be a combination of the component rating and the SSD controller error correction capabilities.

SSD Capacity

SSD capacity is the size of the pool of blocks over which the wear is applied. The capacity is typically larger than the reported capacity of the SSD and smaller than the total physical NAND capacity. The capacity should be de-rated by the number of defective blocks at the end of SSD's life.

SSD Endurance Measurement

The SSD endurance measurement is based on the fundamental relationship describing the number of cycles that are put on the most-cycled block in an SSD for a given workload. This relationship is described as below.

$$NANDCycles = \frac{(HostWrites) \times (WriteAmplificationFactor)}{(SSDCapacity) \times (WearLevelingEfficiency)}$$

Because NAND cycles may not be helpful to conveniently express expected endurance, the fundamental cycling equation is re-factored as below.

$$HostWrites = \frac{(NANDCycles) \times (SSDCapacity) \times (WearLevelingEfficiency)}{(WriteAmplificationFactor)}$$

SSD Endurance Measurement Example

Assume a particular SSD has the following characteristics as measured using the methods described in the earlier sections of this paper:

- SSD Capacity = 8 GB
- NAND max cycles = 3,000
- Write Amplification Factor = 4.33
- Wear Leveling Efficiency = 0.85
- Endurance Measurement : A. Daily Work Load = 8GB
B. Rated life = 2 years

In the equation for host writes yields the following:

$$HostWrites = \frac{(3000cycles) * (8GB) * (0.85)}{4.33}$$

$$HostWrites = 4711.316 \text{ GB}$$

$$TBW = 4.71 \text{ TB}$$

Daily work load is 8GB:

$$\text{Year (365Days)} = \frac{(HostWrites)}{(8) * (365)} = \frac{(4711.316GB)}{(8) * (365)} = 1.61$$

The SSD endurance is expressed as maximum average host writes per day for the rated life of the drive. Therefore, for a drive with a rated life of 2 years:

$$Endurance = \frac{(HostWrites)}{(RatedLifeYears) * (365)}$$

$$Endurance = \frac{(4711.316GB)}{(2) * (365)} = 6.45GB / Day$$

The hypothetical SSD in the example above has a maximum average writes of 6.45GB per day for its rated life-span of 2 years with a workload representative of that used to measure the core SSD endurance parameters.

Apacer Industrial SD/MicroSDHC H1-M endurance estimation results

Flash Type		MLC			
NAND max cycle ^{*1}		3,000			
Capacity	WLE ^{*2}	WAF ^{*2}	TBW	Rated life (Year)	WorkLoad (GB/day)
4 GB	0.85	4.33	2.36	2	3.23
8 GB			4.71		6.45
16 GB			9.42		12.91
32 GB			18.85		25.82
64 GB			37.69		51.63
128 GB			75.38		103.26

* The estimated values are based on sequential write behavior.

(BurnInTest V6.0 Pro, test mode – sequential data pattern, file size – 10.00% of disk space)

1. Flash vendor guaranteed MLC P/E cycle : Toshiba - 3K

2. The WLE/WAF values may vary with the real application on user platform.

3. 1 Terabyte = 1000 GB

Revision History

Revision	Date	Description	Remark
1.0	04/08/2015	First released	

Apacer Technology Inc.

1F., No.32., Zhongcheng Rd.,
Tucheng Dist., New Taipei City 236, Taiwan R.O.C
Tel: +886-2-2267-8000 Fax: +886-2-2267-2261
www.apacer.com

Copyright © 2015 Apacer Technology Inc. All Rights Reserved.
Information in this document is subject to change without prior notice.
Apacer and the Apacer logo are trademarks or registered trademarks of Apacer Technology Inc.
Other brands, names, trademarks or registered trademarks may be claimed as the property of
their respective owners.