Apacer AS510S

The Speedy and Reliable Companion

for PC and Notebooks

Apacer AS510S solid state drive (SSD) is a speedy and reliable companion for consumer PC and laptops. Designed in SATA 6 Gb/s interface, the drive can deliver outstanding performance up to 545 MB/s data transfer speed, highly suitable to serve as operating system boot drive or storage media of important data. Power efficiency wise, AS510S supports SATA power management modes which greatly cut power consumptions to make it an environmental and economical storage drive than traditional hard disk drives.

In addition, enhanced data integrity is enabled by a powerful ECC engine in the device correcting up to 72bit per 1KB data. With the advantages mentioned above, AS510S is proved to be the ideal companion for PC and laptop users.



Dacer

- Operating system boot drive for PC/NB
- Network servers
- Industrial PCs
- Graphic and video applications
- Kiosk, POS and automation.
- Multimedia
- Gaming

Features:

- SATA 6.0 Gb/s interface compliance
- Outstanding read/write performance
- Supports SATA Power Management
- Powerful ECC engine correcting up to 72bit/1KB
- Supports S.M.A.R.T. commands
- TRIM



Apacer Rev. 1.4

© 2015 Apacer Technology Inc.



General Product Specifications

Specifications								
Interface	SATA 6 Gb/s	s interface						
SATA III Burst Speed	600 MB/s							
Capacity*	64, 128, 256 and 480 GB							
Performance**	64 GB	64 GB Read: up to 440 MB/s; Write: up to 205 MB/s						
	128 GB Read: up to 525 MB/s; Write: up to 380 MB/s							
	256 GB	Read: up to 530 MB/s; Write: up to 410 MB/s						
	480 GB Read: up to 545 MB/s; Write: up to 505 MB/s							
Form Factor	2.5 inch							
NAND Flash Media	MLC							
ECC	up to 72bit/1KB							
MTBF	1,000,000 hours (approx.)							
Operating Voltage	5V ± 5%							
	Capacity	Operating	Idle		Partial		Slumber	
Power consumption*** (unit: mA)	64 GB	850	85		20		15	
	128 GB	870	85		20		15	
	256 GB	900	85		20		15	
	480 GB	1142	58		14		11	
Dimension	100.10mm(L) x 69.85mm(W) x 7.00mm(H)							
Endurance****	64 GB	128 GB 256		256 0	GB 4		-80 GB	
	158 TBW	317 TBW 670		670 1	TBW		1370TBW	
Reliability Features	S.M.A.R.T, TRIM, Wear-leveling							
Temperature	Operating	0°C to 70°C						
	Storage	-40 ~ +85 °C						
Humidity	RH 90% under 40°C							
Shock****	500G/2ms							
Vibration****	80 - 2000Hz/20G							
Acoustic	0dB							
Warranty	3 years							
Package Content	Retail package							
Certifications	RoHS, CE, FCC, BSMI							

Global Offices

Taiwan (HQ)

Apacer Technology Inc. 1F. No.32, Zhongcheng Rd. Tucheng Dist., New Taipei City Taiwan 221 R.O.C. Tel: +886-2-2267-8000 Fax: +886-2-2267-2261 amtsales@apacer.com

U.S.A

Apacer Memory America, Inc. 386 Fairview Way, Suite102, Milpitas, CA 95035 Tel: 1-408-518-8699 Fax: 1-408-935-9611 sa@apacerus.com

<u>Japan</u>

Apacer Technology Corp. 5F, Matsura Bldg., Shiba, Minato-Ku Tokyo, 105-0014, Japan Tel: 81-3-5419-2668 Fax: 81-3-5419-0018 jpservices@apacer.com

Europe

Apacer Technology B.V. Science Park Eindhoven 5051 5692 EB Son, The Netherlands Tel: 31-40-267-0000 Fax: 31-40-267-0000#6199 sale@apacer.nl

<u>China</u>

Apacer Electronic (Shanghai) Co., Ltd 1301, No.251, Xiaomuqiao Road, Shanghai, 200032, China Tel: 86-21-5529-0222 Fax: 86-21-5206-6939 sales@apacer.com.cn

India

Apacer Technologies Pvt Ltd, # 535, 1st Floor, 8th cross, JP Nagar 3rd Phase, Bangalore – 560078, India Tel: 91-80-4152-9061 Sales_india@apacer.com

Apacer

Rev. 1.5

*Unformatted. Theoretically, 1GB=1,000,000,000 Bytes. Under operating systems, the capacity might appear to be less than the theoretical capacity because the calculation in OS is based on 1 GB = 1024 MB / 1MB = 1024KB and a minority of the capacity is reserved for maintenance purposes. **Performance results may vary from flash configurations or host system settings. Test results are based on ATTO

platform.

Power consumption were measured at 5.0V and results may vary from flash configurations or host system settings. ***Estimated under typical PC user behaviors, NAND endurance cycles, write amplification and wear leveling factors. ******Shock and vibrations are subject to change without notice

© 2015 Apacer Technology Inc.



Apacer Rev. 1.5

Ordering Information

Capacity	Bulk	Distributor/Retailer
64 GB	AP64GAS510SB	AP64GAS510SB-1
128 GB	AP128GAS510SB	AP128GAS510SB-1
256 GB	AP256GAS510SB	AP256GAS510SB-1
480 GB	AP480GAS510SB	AP480GAS510SB-1

Revision History

Version	Description	Date
0.1	Preliminary release	02/15/2013
0.2	Added Ordering Information	02/26/2013
0.3	Added TBW	03/01/2013
0.4	Added performance information for 256GB	03/12/2013
1.0	Official release	04/03/2013
1.1	Warranty is extended to 3 years	05/21/2013
1.2	Model name renamed as AS510S	06/19/2013
1.3	Removed AES-256 information	08/18/2014
1.4	Added BSMI certification	08/20/2014
1.5	Added 480 GB to capacity list	01/19/2015

Apacer Technology Inc.

1F., No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City Tel: +886-2-2267-8000 Fax: +886-2-2267-2261

www.apacer.com

Copyright ©2015 Apacer Technology Inc. All Rights Reserved. Information in this document is subject to change without prior notice. Apacer and the Apacer logo are trademarks or registered trademarks of Apacer Technology Inc. Other brands, names, trademarks or registered trademarks may be claimed as the property of their respective owners.

© 2015 Apacer Technology Inc.