

Apacer AST680S

The Speedy and Reliable Companion

for PC and Notebooks

Apacer AST680S solid state drive (SSD) is a speedy and reliable companion for consumer PC and laptops. Designed in SATA 6 Gb/s interface, the drive can deliver outstanding performance up to 525 MB/s data transfer speed, highly suitable to serve as operating system boot drive or storage media of important data. Power efficiency wise, AST680S supports SATA power management modes which greatly cut power consumptions to make it an environmental and economical storage drive than traditional hard disk drives.

In addition, enhanced data integrity is enabled by a powerful ECC engine in the device correcting up to 120bit per 2KB data. With the advantages mentioned above, AST680S is proved to be the ideal companion for PC and laptop users.



Applications

- PC/NB for general storage
- Operating system boot drive for PC/NB
- Network servers
- Industrial PCs
- Graphic and video applications
- Kiosk, POS and automation.
- Multimedia
- Gaming

Features:

- SATA 6.0 Gb/s interface compliance
- Outstanding read/write performance
- Supports SATA Power Management
- Powerful ECC engine correcting up to 120bit/2KB
- Supports S.M.A.R.T. commands
- TRIM







© 2015 Apacer Technology Inc.

acer

SATA SSD **AST680S**

General Product Specifications

Specifications					
Interface	SATA 6 Gb/s interface				
SATA III Burst Speed	600 MB/s				
Capacity*	240GB \ 480 GB				
Performance**	240 GB Read: up to 520 MB/s; Write: up to 500 MB/s				
	480 GB Read: up to 525 MB/s; Write: up to 500 MB/s				
Form Factor	2.5 inch				
NAND Flash Media	TLC				
ECC	up to 72bit/1KB				
MTBF	1,000,000 hours (approx.)				
Operating Voltage	$5V \pm 5\%$				
Power consumption*** (unit: mA)	Capacity	Operating	Idle	Partial	Slumber
	240 GB	3350	645	530	530
	480 GB	3680	655	535	535
Dimension	100.10mm(L) x 69.85mm(W) x 7.00mm(H)				
Reliability Features	S.M.A.R.T, TRIM, Wear-leveling				
Temperature	Operating	0°C to 70°C			
	Storage	-40 ~ +85 °C			
Humidity	RH 90% under 40°C				
Shock****	500G/2ms				
Vibration****	80 – 2000Hz/20G				
Acoustic	0dB				
Warranty	3 years				
Package Content	Retail package				
Certifications	RoHS, CE, FCC, BSMI				

Global Offices

Taiwan (HQ)

Apacer Technology Inc. 1F. No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City Taiwan 221 R.O.C. Tel: +886-2-2267-8000 Fax: +886-2-2267-2261 amtsales@apacer.com

<u>U.S.A</u>

Apacer Memory America, Inc. 46732 Lakeview Blvd., Fremont, CA 94538 Tel: 1-408-518-8699 Fax: 1-510-249-9568 sa@apacerus.com

Japan

Apacer Technology Corp. 5F, Matsura Bldg., Shiba, Minato-Ku Tokyo, 105-0014, Japan Tel: 81-3-5419-2668 Fax: 81-3-5419-0018 ips<u>ervices@apacer.com</u>

Europe

Apacer Technology B.V. Science Park Eindhoven 5051 5692 EB Son, The Netherlands Tel: 31-40-267-0000 Fax: 31-40-267-0000#6199 sale@apacer.nl

China

Apacer Electronic (Shanghai) Co., Ltd Room D,22/FL,No2,Lane600,JieyunPlaza, Tianshan RD,Shanghai,200051,China Tel: 86-21-6228-9939 Fax: 86-21-6228-9936 sales@apacer.com.cn

India

Apacer Technologies Pvt Ltd, Unit No.201. "Brigade Corner"

7th Block Jayanagar, Yediyur Circle, Bangalore – 560082, INDIA. Tel: +91-80-4152-9061/62/63 Fax:+91-80-4170-0215 Sales_india@apacer.com

Apacer Rev. 1.2

*Unformatted. Theoretically, 1GB=1,000,000,000 Bytes. Under operating systems, the capacity might appear to be less than the theoretical capacity because the calculation in OS is based on 1 GB = 1024 MB / 1MB =1024KB and a minority of the capacity is reserved for maintenance purposes. **Performance results may vary from flash configurations or host system settings. Test results are based on ATTO

platform.

*Power consumption were measured at 5.0V and results may vary from flash configurations or host system settings. ****Shock and vibrations are subject to change without notice



© 2015 Apacer Technology Inc.



Ordering Information

Capacity	Bulk	Distributor/Retailer	
240 GB	AP240GT680SB	AP240GAST680S-1	
480 GB	AP480GT680SB	AP480GAST680S-1	

Revision History

Version	Description	Date
1.0	First release	04/24/2015
1.1	Changed product drawing	04/28/2015
1.2	Revised ordering information	08/21/2015

Apacer Technology Inc.

1F., No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City Tel: +886-2-2267-8000 Fax: +886-2-2267-2261

www.apacer.com

Copyright ©2015 Apacer Technology Inc. All Rights Reserved. Information in this document is subject to change without prior notice. Apacer and the Apacer logo are trademarks or registered trademarks of Apacer Technology Inc. Other brands, names, trademarks or registered trademarks may be claimed as the property of their respective owners. Apacer Rev. 1.2

© 2015 Apacer Technology Inc.