

RoHS Compliant

USB Flash Drive

EH353 Product Specifications





December 19, 2017 Version 2.5



Apacer Technology Inc.

1F, No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City, Taiwan, R.O.C Tel: +886-2-2267-8000 Fax: +886-2-2267-2261 www.apacer.com

Features:

- USB3.0 Super Speed compatible, and backward compatible with USB2.0 & USB1.1 interfaces
 - USB3.0 max. transfer rate: 5.0 Gbps
 - Backward compatible with 480Mbps & 12 Mbps
- Capacity
 - SLC: 256, 512 MB
 1, 2, 4, 8, 16, 32 GB
 - MLC: 8, 16, 32, 64, 128 GB
- Performance*

SLC

- Sequential read: up to 80 MB/s
- Sequential write: up to 70 MB/s

MLC

- Sequential read: up to 205 MB/s
- Sequential write: up to 95 MB/s
- Endurance (in Terabytes Written: TBW)

SLC

- 256 MB: 2 TBW
- 512 MB: 5 TBW
- 1 GB: 11 TBW
- 2 GB: 22 TBW
- 4 GB: 44 TBW
- 8 GB: 88 TBW
- 16 GB: 176 TBW
- 32 GB: 352 TBW

MLC

- 8 GB: 6 TBW
- 16 GB: 13 TBW
- 32 GB: 29 TBW
- 64 GB: 26 TBW
- 128 GB: 66 TBW

Temperature Range

- Operating:
 Standard: 0°C to 70°C
 Extended: -40°C to 85°C
- Storage: -40°C to 100°C

Flash Management

- Flash bad-block management
- Built-in hardware ECC
- Power saving implemented
- Wear-leveling algorithms
- S.M.A.R.T.
- Power Failure Management

Power Consumption*

- Operating voltage: 5V

SLC

- Active mode: 225 mA
- Idle mode: 65 mA

MLC

- Active mode: 275 mA
- Idle mode: 80 mA
- OS Support
 - Windows: WinXP/7 or later
 - Mac: 10.2.8 or later
 - Linux: 2.4.10 or later
- USB Bus-Powered Capability
- NAND Flash Type: MLC/SLC
- Dimensions: 59.0 x 18.4 x 9.1, unit: mm

1

RoHS Compliant

*Varies from capacities. The values for performances and power consumptions presented are typical and may vary depending on flash configurations or platform settings.

2

Table of Contents

ļ

1. General Descriptions

Apacer USB3.0 Handy FLASH Drive EH353 is a ultra high-performance flash disk drive designed offering portable storage solutions or external memory expansion. This new generation USB flash drive is compatible with the latest USB specification – USB3.0 Super Speed, with a maximum transfer rate of 5.0 Gbps. The connector is backward employable with USB2.0 and USB1.1 interfaces as well. With compliance with USB3.0 specification, this USB drive can deliver up to 275 MB/s outstanding performance. Reliability wise, the USB comes with various implementations including powerful hardware ECC engine, power saving modes, wear leveling and flash block management. This product is well suited for portable flash storage applications while operating at minimal power consumption.

1.1 Performance-Optimized USB Controller

1.1.1 Power Saving Implemented

The internal controller of the USB model is designed with power saving implementations, allowing the device to operate at low power consumption.

1.1.2 Program RAM Architect

The internal Program RAM implementation allows the host to upgrade firmware codes anytime when needed.

1.1.3 Error Correction Code (ECC)

The UFD utilizes 1-bit Error Detection Code (EDC) and Error Correction Code (ECC).

1.1.4 Flash Block Management

Current production technology is unable to guarantee total reliability of NAND flash memory array. When a flash memory device leaves factory, it comes with a minimal number of initial bad blocks during production or out-of-factory as there is no currently known technology that produce flash chips free of bad blocks. In addition, bad blocks may develop during program/erase cycles. When host performs program/erase command on a block, bad block may appear in Status Register. Since bad blocks are inevitable, the solution is to keep them in control. Apacer flash devices are programmed with ECC and block mapping technique to reduce invalidity or error. Once bad blocks are detected, data in those blocks will be transferred to free blocks and error will be corrected by designated algorithms.

1.1.5 Wear-Leveling Algorithms

Flash memory devices differ from Hard Disk Drives (HDDs) in terms of how blocks are utilized. For HDDs, when a change is made to stored data, like erase or update, the controller mechanism on HDDs will perform overwrites on blocks. Unlike HDDs, flash blocks cannot be overwritten and each P/E cycle wears down the lifespan of blocks gradually. Repeatedly program/erase cycles performed on the same memory cells will eventually cause some blocks to age faster than others. This would bring flash storages to their end of service term sooner. Wear leveling is an important mechanism that level out the wearing of blocks so that the wearing-down of blocks can be almost evenly distributed. This will increase the lifespan of flash drives. Commonly used wear leveling types are Static and Dynamic.

1.1.6 S.M.A.R.T.

S.M.A.R.T. is an abbreviation for Self-Monitoring, Analysis and Reporting Technology, a selfmonitoring system that provides indicators of drive health as well as potential disk problems. It serves as a warning for users from unscheduled downtime by monitoring and displaying critical drive information. Ideally, this should allow taking proactive actions to prevent drive failure and make use of S.M.A.R.T. information for future product development reference.

1.1.7 Power Failure Management

Power disruption may occur when users are storing data into the SSD. In this urgent situation, the controller would protect firmware table and the data written to flash from data loss in the event of power off. Apacer power failure management maintains data correctness and increases the reliability of the data stored in the NAND Flash memory.

2. Product & Environmental Specifications

2.1 SLC

Item		Specifications								
Interface		Super-speed USB3.0 compliant; backward compatible with USB2.0 and USB1.1								
			256MB	512MB	1GB	2GB	4GB	8GB	16GB	32GB
Performance*	(MB/s)	Read	60	60	65	65	65	80	80	80
		Write	10	21	40	40	50	65	70	70
Power Consumption**		Active: 2 Idle: 65	225 mA mA							
MTBF		2,000,0	00 hours							
Tomporatura	Operating	0°C to 70°C (Standard); -40°C to 85°C (Extended)								
remperature	Storage	-40°C to	-40°C to 100°C							
Humidity		30°C to 60°C , 95% RH; 244hrs (compliant with MIL-STD-810G)								
Chaoli	Operating	50(G)/11(ms)/half sine (compliant with MIL-STD-202G)								
Non-operating		1,500(G)/0.5(ms)/half sine (compliant with MIL-STD-202G)								
Vibration	Operating	7.69(Gr	ms), 20~20	00(Hz)/ran	dom (cor	mpliant w	ith MIL-S	TD-8100	3)	
VIDIATION	Non-operating	4.02(Gr	ms), 15~20	00(Hz)/ran	dom (cor	mpliant w	ith MIL-S	STD-8100	G)	
ESD CE compliance (Criteria B)										

Table 2-1 Product & Environmental Specifications (SLC)

Note:

Results may vary from flash configurations or host system settings. *Sequential performance is based on CrystalDiskMark 5.2.1 with file size 1,000MB. **Active power is an average power measurement performed using CrystalDiskMark with 128KB sequential read/write transfers.

2.2 MLC

Table 2-2 Product & Environmental Specifications (MLC)

Item					Speci	fications			
Interface		Super-spe USB1.1	ed US	B3.0 co	ompliant; ba	ckward com	npatible with	USB2.	0 and
			8G	B***	16GB	32GB	64GB	1280	B****
Performance*		Read	205	95	190	190	185	190	195
		Write	20	29	55	45	95	95	80
			8G	B***	16GB	32GB	64GB	128G	B****
Power consur	nption**	Active	165	150	270	265	275	265	175
		Idle	75	50	85	80	80	55	35
MTBF		1,000,000 hours							
Tomporaturo	Operating	0°C to 70°C (Standard); -40°C to 85°C (Extended)							
remperature	Storage	-40°C to 100°C							
Humidity		30°C to 60°C , 95% RH; 244hrs (compliant with MIL-STD-810G)							
Operating		50(G)/11(ms)/half sine (compliant with MIL-STD-202G)							
SHUCK	Non-operating	1,500(G)/0	1,500(G)/0.5(ms)/half sine (compliant with MIL-STD-202G)						
Vibration	Operating	7.69(Grms), 20~2	000(Hz)	/random (cor	mpliant with N	/IL-STD-810G	i)	
vibration	Non-operating	4.02(Grms	4.02(Grms), 15~2000(Hz)/random (compliant with MIL-STD-810G)						
ESD		CE complia	ance (C	riteria B	5)				

Note:

Note: Results may vary from flash configurations or host system settings. *Sequential performance is based on CrystalDiskMark 5.2.1 with file size 1,000MB. **Active power is an average power measurement performed using CrystalDiskMark with 128KB sequential read/write transfers. ***Values on the left are measured on 32Gb x2 while those on the right are measured on 64Gb x1. ****Values on the left are measured on 512Gb x2 while those on the right are measured on 1Tb x1.

7

2.3 Endurance

The endurance of a storage device is predicted by TeraBytes Written based on several factors related to usage, such as the amount of data written into the drive, block management conditions, and daily workload for the drive. Thus, key factors, such as Write Amplifications and the number of P/E cycles, can influence the lifespan of the drive.

Capacity	TeraBytes Written
256 MB	2
512 MB	5
1 GB	11
2 GB	22
4 GB	44
8 GB	88
16 GB	176
32 GB	352

Table 2-3	Endurance	Specifications	(SLC	;)
-----------	-----------	----------------	------	----

Table 2-4 Endurance Specifications (MLC)

Capacity	TeraBytes Written
8 GB	6
16 GB	13
32 GB	29
64 GB	26
128 GB	66

Note:

- The estimated values are based on sequential write behavior. (Apacer EDTest Tool, test mode sequential data pattern 100.00% of disk space)
- Flash vendor guaranteed MLC P/E cycle: Toshiba 3K.
- The WLE/WAF values may vary with the real application on user platform.
- 1 Terabyte = 1,000 GB.

3. Absolute Maximum Rating

Caution: Absolute Maximum Stress Ratings – Applied conditions greater than those listed under "Absolute Maximum Stress Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these conditions or conditions greater than those defined in the operational sections of this data sheet is not implied. Exposure to absolute maximum stress rating conditions may affect device reliability.

Table 3-1 Absolute	Stress Rating
--------------------	---------------

Item	Range
Required power supply	4.5-5.5V
Operating temperature	0°C to 70°C (Standard); -40°C to 85°C (Extended)
Storage temperature	-40°C to 100°C

4. Physical Dimensions



Unit: mm

5. Product Ordering Information



5.2 Valid Combinations

5.2.1 EH353 (SLC)

• Orange Housing

Capacity	Standard Temperature	Extended Temperature
256MB	APHA256MAG0CG-2T	APHA256MAG0EG-2T
512MB	APHA512MAG0CG-2T	APHA512MAG0EG-2T
1GB	APHA001GAG0CG-2T	APHA001GAG0EG-2T
2GB	APHA002GAG0CG-2T	APHA002GAG0EG-2T
4GB	APHA004GAG0CG-2T	APHA004GAG0EG-2T
8GB	APHA008GAG0CG-2T	APHA008GAG0EG-2T
16GB	APHA016GAG0CG-2T	APHA016GAG0EG-2T
32GB	APHA032GAG0CG-2T	APHA032GAG0EG-2T

Black Housing

Capacity	Standard Temperature	Extended Temperature
256MB	APHA256MAK0CG-2T	APHA256MAK0EG-2T
512MB	APHA512MAK0CG-2T	APHA512MAK0EG-2T
1GB	APHA001GAK0CG-2T	APHA001GAK0EG-2T
2GB	APHA002GAK0CG-2T	APHA002GAK0EG-2T
4GB	APHA004GAK0CG-2T	APHA004GAK0EG-2T
8GB	APHA008GAK0CG-2T	APHA008GAK0EG-2T
16GB	APHA016GAK0CG-2T	APHA016GAK0EG-2T
32GB	APHA032GAK0CG-2T	APHA032GAK0EG-2T



5.2.2 EH353 (MLC)

• Orange Housing

Capacity	Standard Temperature	Extended Temperature
8GB	APHA008GAG0CG-3TM	APHA008GAG0EG-3TM
16GB	APHA016GAG0CG-3TM	APHA016GAG0EG-3TM
32GB	APHA032GAG0CG-3TM	APHA032GAG0EG-3TM
64GB	APHA064GAG0CG-3TM	APHA064GAG0EG-3TM
12000		APHA128GAG0EG-3TM*
120GB	APTA 120GAGUCG-31M	APHA128G4MCEG-3TM**

Black Housing

Capacity	Standard Temperature	Extended Temperature
8GB	APHA008GAK0CG-3TM	APHA008GAK0EG-3TM
16GB	APHA016GAK0CG-3TM	APHA016GAK0EG-3TM
32GB	APHA032GAK0CG-3TM	APHA032GAK0EG-3TM
64GB	APHA064GAK0CG-3TM	APHA064GAK0EG-3TM
120CD		APHA128GAK0EG-3TM*
120GD	AFRA126GARUCG-31W	APHA128G4KCEG-3TM**

Note: The part number with one asterisk represents the SSD manufactured based on 512Gb x2 while that with two asterisks based on 1Tb x1.

Revisio	n History

Revision	Description	Date
1.0	Official release	7/24/2015
1.1	- Modified performance and power consumption data for MLC models.	9/17/2015
1.2	Revised product ordering information.	10/14/2015
1.3	Revised mechanical specifications	12/21/2015
1.4	 Added 128GB support Added OS support and flash management implementations on Features page 	2/19/2016
1.5	Revised performance for MLC series (8GB-64GB)	2/26/2016
1.6	Revised read performance for MLC 16GB	3/31/2016
1.7	Added S.M.A.R.T. and Power Failure Management to Features	10/3/2016
1.8	Added environmental specifications	10/18/2016
1.9	 Added extended temperature Revised storage temperature 	12/13/2016
2.0	Added 64Gbx1 on 8G performance and power consumption for MLC	4/18/2017
2.1	Added 1Tbx1 on 128G performance and power consumption for MLC	7/11/2017
2.2	Updated product ordering information for 128GB	7/24/2017
2.3	Updated product ordering information for 128GB manufactured based on 512Gb x2 (Orange Housing)	8/9/2017
2.4	Updated product ordering information for 128GB with standard temperature support (Orange Housing)	8/10/2017
2.5	Added 2.3 Endurance	12/19/2017

Global Presence

Taiwan (Headquarters)

Apacer Technology Inc. 1F., No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City 236, Taiwan R.O.C. Tel: 886-2-2267-8000 Fax: 886-2-2267-2261 amtsales@apacer.com

Japan

Apacer Technology Corp. 5F, Matsura Bldg., Shiba, Minato-Ku Tokyo, 105-0014, Japan Tel: 81-3-5419-2668 Fax: 81-3-5419-0018 jpservices@apacer.com

China

Apacer Electronic (Shanghai) Co., Ltd Room D, 22/FL, No.2, Lane 600, JieyunPlaza, Tianshan RD, Shanghai, 200051, China Tel: 86-21-6228-9939

Fax: 86-21-6228-9936 sales@apacer.com.cn **U.S.A. Apacer Memory America, Inc.** 46732 Lakeview Blvd., Fremont, CA 94538 Tel: 1-408-518-8699 Fax: 1-510-249-9551 <u>sa@apacerus.com</u>

Europe

Apace Technology B.V. Science Park Eindhoven 5051 5692 EB Son, The Netherlands Tel: 31-40-267-0000 Fax: 31-40-290-0686 sales@apacer.nl

India

Apacer Technologies Pvt Ltd, Unit No.201, "Brigade Corner", 7th Block Jayanagar, Yediyur Circle, Bangalore – 560082, India Tel: 91-80-4152-9061 Fax: 91-80-4170-0215 sales_india@apacer.com